


# 38 SPECIAL NONTOX

## TFMJ 158 GRS SB38NT



After firing the cartridge is free from toxic exposure to barium, lead, mercury, antimony. It does not pollute the environment, does not endanger the shooter's health with combustion products, and does not leave harmful residue in the gun. It ensures safe shooting in closed premises and on target ranges. Unique patented primer design.



### BALLISTICS

		MUZZLE	25	50	100
DISTANCE	y				
VELOCITY	fps	873	855	838	806
ENERGY	ft-lb	267	256	246	228
DISTANCE	y	12.5	25	50	100
POINTS OF IMPACT	in	0.1	0.1	-2.4	-18.9

### PROPERTIES

BULLET	TYPE	TFMJ	
	WEIGHT	grs	158
	DIAMETER	in	0.357
	SECTIONAL DENSITY	lb/in <sup>2</sup>	0.177
	MATERIAL OF JACKET	CuZn 30	
BALLISTIC COEFFICIENT		G1	0.184
PRIMER	TYPE	Boxer	
	STYLE	Small Pistol Primer	
CARTRIDGE	LENGTH	in	1.520
CASINGS	Factory Brass		
POWER FACTOR ESTIMATED	kgr-fps	137.9	
+P AMMUNITION	No		
TEST BARREL LENGTH	in	7½	
SUGGESTED USE	Range, Match/Competition		
FEATURES	Fully Encapsulated Bullet, Reliable Functioning, Non-expanding, No Barrel Leading		

### PACKAGING

BOXES PER CASE	20
WEIGHT PER CASE	lb 36

