


9 × 21 NONTOX TFMJ V311702 124 GRS



After firing the cartridge is free from toxic exposure to barium, lead, mercury, antimony. It does not pollute the environment, does not endanger the shooter's health with combustion products, and does not leave harmful residue in the gun. It ensures safe shooting in closed premises and on target ranges. Unique patented primer design.



PROPERTIES

BULLET	TYPE		TFMJ
	WEIGHT	grs	124
	DIAMETER	in	N/A
	SECTIONAL DENSITY	lb/in ²	N/A
	MATERIAL OF JACKET		CuZn 30
BALLISTIC COEFFICIENT		G1	0.152
PRIMER	TYPE		N/A
	STYLE		N/A
CARTRIDGE	LENGTH	in	1.171
CASINGS			N/A
POWER FACTOR ESTIMATED		kgf-fps	147.3
+P AMMUNITION			No
TEST BARREL LENGTH		in	5
SUGGESTED USE			N/A
FEATURES			N/A
PACKAGING			
BOXES PER CASE			20
WEIGHT PER CASE		lb	30

BALLISTICS

DISTANCE	y	MUZZLE	25	50	100
VELOCITY	fps	1,188	1,125	1,074	994
ENERGY	ft-lb	388	349	317	272
DISTANCE	y	12.5	25	50	100
POINTS OF IMPACT	in	-0.1	0.0	-1.1	-9.6

