

# 40 S&W

## XRG-D

130 GRS  
SB40XA



This solid copper hollow-point bullet construction results in near 100% weight retention regardless of the barriers encountered. Light-for-caliber bullet weights produce low perceived recoil, high velocity, and reliable expansion from today's compact personal defense handguns. The impressive, real-world performance of XRG Defense has been proven by many European Law Enforcement units.



### PROPERTIES

|                        |                    |                    |       |
|------------------------|--------------------|--------------------|-------|
| BULLET                 | TYPE               |                    | XRG-D |
|                        | WEIGHT             | grs                | 130   |
|                        | DIAMETER           | in                 | N/A   |
|                        | SECTIONAL DENSITY  | lb/in <sup>2</sup> | N/A   |
|                        | MATERIAL OF JACKET |                    | -     |
| BALLISTIC COEFFICIENT  | G1                 |                    | 0.130 |
| PRIMER                 | TYPE               |                    | N/A   |
|                        | STYLE              |                    | N/A   |
| CARTRIDGE              | LENGTH             | in                 | 1.134 |
| CASINGS                |                    |                    | N/A   |
| POWER FACTOR ESTIMATED |                    | kgf·fps            | 162.1 |
| +P AMMUNITION          |                    |                    | No    |
| TEST BARREL LENGTH     |                    | in                 | 6     |
| SUGGESTED USE          |                    |                    | N/A   |
| FEATURES               |                    |                    | N/A   |
| PACKAGING              |                    |                    |       |
| BOXES PER CASE         |                    |                    | 40    |
| WEIGHT PER CASE        |                    | lb                 | 33.7  |

### BALLISTICS

|                  |       |        |       |       |       |      |
|------------------|-------|--------|-------|-------|-------|------|
| DISTANCE         | y     | MUZZLE | 25    | 50    | 100   |      |
| VELOCITY         | fps   |        | 1,247 | 1,164 | 1,097 | 999  |
| ENERGY           | ft·lb |        | 449   | 391   | 347   | 288  |
| DISTANCE         | y     |        | 12.5  | 25    | 50    | 100  |
| POINTS OF IMPACT | in    |        | -0.6  | 0.0   | -1.0  | -8.6 |

