



10 mm AUTO

XRG-D 130 GRS SB10XA

This solid copper hollow-point bullet construction results in near 100% weight retention regardless of the barriers encountered. Light-for-caliber bullet weights produce low perceived recoil, high velocity, and reliable expansion from today's compact personal defense handguns. The impressive, real-world performance of XRG Defense has been proven by many European Law Enforcement units.



PROPERTIES

| | | | |
|------------------------|--------------------|--------------------|-------|
| BULLET | TYPE | | XRG-D |
| | WEIGHT | grs | 130 |
| | DIAMETER | in | N/A |
| | SECTIONAL DENSITY | lb/in ³ | N/A |
| | MATERIAL OF JACKET | | - |
| BALLISTIC COEFFICIENT | G1 | | 0.130 |
| PRIMER | TYPE | | N/A |
| | STYLE | | N/A |
| CARTRIDGE | LENGTH | in | 1.260 |
| CASINGS | | | N/A |
| POWER FACTOR ESTIMATED | | kgf·fps | 177.1 |
| +P AMMUNITION | | | No |
| TEST BARREL LENGTH | | in | 6 |
| SUGGESTED USE | | | N/A |
| FEATURES | | | N/A |
| PACKAGING | | | |
| BOXES PER CASE | | | 40 |
| WEIGHT PER CASE | | lb | 33.9 |

BALLISTICS

| | | | | | | |
|------------------|-------|--------|-------|-------|-------|-------|
| DISTANCE | y | MUZZLE | 25 | 50 | 100 | |
| VELOCITY | fps | | 1,362 | 1,262 | 1,177 | 1,051 |
| ENERGY | ft·lb | | 535 | 460 | 400 | 319 |
| DISTANCE | y | | 12.5 | 25 | 50 | 100 |
| POINTS OF IMPACT | in | | -0.6 | 0.0 | -0.8 | -7.2 |

