

7 × 64

FMJ

V331162
140 GRS



Full Metal Jacket bullet. Standard lead core with a metallic jacket. Best for training and target shooting applications.



PROPERTIES

| | | | |
|------------------------|--------------------|--------------------|---------|
| BULLET | TYPE | | FMJ |
| | WEIGHT | grs | 140 |
| | DIAMETER | in | 0.284 |
| | SECTIONAL DENSITY | lb/in ² | 0.248 |
| | MATERIAL OF JACKET | | CuZn 10 |
| BALLISTIC COEFFICIENT | | G1 | 0.429 |
| | | G7 | 0.214 |
| CARTRIDGE | LENGTH | in | 3.307 |
| POWER FACTOR ESTIMATED | | kgr-fps | 388.1 |
| TEST BARREL LENGTH | | in | 23½ |
| SUGGESTED USE | | | N/A |
| FEATURES | | | N/A |

PACKAGING

| | | | |
|-----------------|--|----|------|
| BOXES PER CASE | | | 20 |
| WEIGHT PER CASE | | lb | 24.5 |

BALLISTICS

| | | | | | | |
|------------------|-------|--------|-------|-------|-------|-------|
| DISTANCE | y | MUZZLE | 100 | 200 | 300 | 400 |
| VELOCITY | fps | 2,772 | 2,557 | 2,352 | 2,156 | 1,970 |
| ENERGY | ft-lb | 2,389 | 2,033 | 1,719 | 1,445 | 1,207 |
| DISTANCE | y | 50 | 100 | 200 | 300 | 400 |
| POINTS OF IMPACT | in | -0.4 | 0.0 | -3.3 | -13.0 | -30.1 |

